

# Nivo M+ Series Total Stations



Datasheet

**NEW**  
FOR  
2015



**Simply Reliable Value**

## Key Features

- **2", 3" and 5" angle accuracies**
- **Intuitive onboard field software**
- **25,000 point storage**
- **Reflectorless measurement up to 500m (1,640 ft)**
- **Hot swappable batteries**
- **Laser pointer**
- **USB port for convenient data transfer**
- **Bluetooth**
- **Optional laser plummet**

## Nivo M+ Series

The Nivo M+ instruments are compact, lightweight and ultra-rugged for use on any work site in all dust, dirt and weather conditions. The fast, long range EDM measures in both prism and reflectorless modes with both being available at the same time and initiated with a single key press.

The Nikon Nivo M+ Series Total Stations feature legendary Nikon optics which effectively let in more light for brighter, sharper images in even the lowest of light conditions. The easy to learn and use Nikon onboard software offers simple data and file management, Quick Codes for easy one-button data collection of point features and a complete set of powerful CoGo functions.

All Nivo M+ models support Bluetooth communications to external devices such as data collectors and have a USB port for portable data transfer via USB stick. In addition, all models come standard with coaxial laser pointers and a traditional optical plummet - which can be upgraded to a laser plummet.

The Nikon Nivo M+ is built tough for all occasions.



NEW  
for 2015

# Nikon Nivo M+ Series Total Stations

## Distance Measurement

Range with Nikon specified prisms (Good conditions) <sup>i</sup>			
With reflector sheet 5 cm x 5 cm (2 in x 2 in)			
Nivo <sup>2,M+</sup> .....			1.5 m to 270 m (4.9 ft to 886 ft)
Nivo <sup>3,M+, Nivo<sup>5,M+</sup></sup>			1.5 m to 300 m (4.9 ft to 984 ft)
With single prism 6.25 cm (2.5 in)			
Nivo <sup>2,M+</sup> .....			1.5 m to 3,000 m (4.9 ft to 9,843 ft)
Nivo <sup>3,M+, Nivo<sup>5,M+</sup></sup>			1.5 m to 5,000 m (4.9 ft to 16,404 ft)
Range reflectorless mode <sup>ii</sup>			
Nivo <sup>2,M+</sup>	Good <sup>j</sup>	Normal <sup>iv</sup>	Difficult <sup>v</sup>
KGC <sup>iii</sup> (18%)	350 m (1,148 ft)	250 m (820 ft)	200 m (656 ft)
KGC <sup>iii</sup> (90%)	500 m (1,640 ft)	400 m (1,312 ft)	250 m (820 ft)
Nivo <sup>3,M+, Nivo<sup>5,M+</sup></sup>	Good <sup>j</sup>	Normal <sup>iv</sup>	Difficult <sup>v</sup>
KGC <sup>iii</sup> (18%)	280 m (920 ft)	250 m (820 ft)	200 m (656 ft)
KGC <sup>iii</sup> (90%)	500 m (1,640 ft)	500 m (1,640 ft)	300 m (984 ft)
Shortest possible range.....			1.5m (4.9 ft)
Accuracy <sup>vi</sup> (Precise mode)			
ISO17123-4			
Prism.....		±(2+2 ppm x D) mm	
Reflectorless.....		±(3+2 ppm x D) mm	

## Measuring interval<sup>vii</sup>

Prism mode	Precise mode	Normal mode
Nivo <sup>2,M+</sup>	1.6 s	0.8 s
Nivo <sup>3,M+, Nivo<sup>5,M+</sup></sup>	1.5 s	0.8 s
Reflectorless mode <sup>viii</sup>		
Nivo <sup>2,M+</sup>	2.1 s	1.2 s
Nivo <sup>3,M+, Nivo<sup>5,M+</sup></sup>	1.8 s	1.0 s
Least count	1 mm (0.002 ft)	10 mm (0.02 ft)

## Angle Measurement

ISO 17123-3 accuracy (horizontal and vertical).....	2"/0.6 mgon Nivo <sup>2,M+</sup> 3"/1 mgon Nivo <sup>3,M+</sup> 5"/1.5 mgon Nivo <sup>5,M+</sup>
Reading system .....	Absolute encoder
Circle diameter .....	62 mm (2.4 in)
Horizontal/Vertical angle .....	Diametrical Nivo <sup>2,M+, Nivo<sup>3,M+</sup> Single Nivo<sup>5,M+</sup></sup>
Minimum increment .....	Degree: 1/5/10" Gon: 0.2/1/2 mgon MIL6400: 0.005/0.02/0.05 mil

## Telescope

Tube length.....	125 mm (4.9 in)	
Image.....	Erect	
Magnification .....	30x (18x/36x with optional eyepieces)	
Nivo <sup>2,M+</sup> Effective diameter of objective .....	40 mm (1.6 in)	
Nivo <sup>2,M+</sup> EDM diameter.....	45 mm (1.8 in)	
Nivo <sup>3,M+, Nivo<sup>5,M+</sup></sup>	Effective diameter of objective .....	45 mm (1.8 in)
Nivo <sup>3,M+, Nivo<sup>5,M+</sup></sup>	EDM diameter .....	50 mm (2.0 in)
Field of view .....	1°20'	
Resolving power .....	3"	
Minimum focusing distance .....	1.5 m (4.9 ft)	
Laser Pointer .....	Coaxial Red Light	

## Tilt Sensor

Type .....	Dual-axis
Method .....	Liquid-electric detection
Compensation range.....	±3.5'

## Communications

Communication ports .....	1 x serial (RS-232C), 1 x USB (host)
Wireless communications .....	integrated Bluetooth

## Power

Internal Li-ion battery (x2)	3.8 V DC
Output voltage.....	
Operating time <sup>x</sup>	
Nivo <sup>2,M+</sup>	approx. 19 hours (continuous distance/angle measurement)
	approx. 57 hours (distance/angle measurement every 30 seconds)
	approx. 62 hours (continuous angle measurement)
Nivo <sup>3,M+, Nivo<sup>5,M+</sup></sup>	approx. 10 hours (continuous distance/angle measurement)
	approx. 26 hours (distance/angle measurement every 30 seconds)
	approx. 31 hours (continuous angle measurement)
Charging time	
Full charge .....	4 hours

## General Specifications

Level vials	10'/2 mm	
Sensitivity of circular level vial .....		
Optical plummet		
Image .....	Erect	
Magnification .....	3x	
Field of view .....	5°	
Focusing range .....	0.5 m (1.6 ft) to ∞	
Display face 1.....	backlit, graphic LCD (128x64 pixel)	
Display face 2.....	backlit, graphic LCD (128x64 pixel)	
Laser plummet (optional)	4 levels	
Point memory .....	25,000 records	
Dimensions (W x D x H) .....	149 mm x 145 mm x 306 mm (5.8 in x 5.7 in x 12.0 in)	
Weight (approx.)		
Nivo <sup>2,M+</sup> Main unit (without batteries) .....	3.8 kg (8.4 lb)	
Nivo <sup>3,M+, Nivo<sup>5,M+</sup></sup>	Main unit (without batteries) .....	3.7 kg (8.1 lb)
Battery .....	0.1 kg (0.2 lb)	
Carrying case .....	2.3 kg (5.1 lb)	

## Environmental

Operating temperature range .....	-20 °C to +50 °C (-4 °F to +122 °F)
Nivo <sup>5,MW+</sup> .....	-30 °C to +50 °C (-22 °F to +122 °F)
Storage temperature range .....	-25 °C to +60 °C (-13°F to +140 °F)
Nivo <sup>5,MW+</sup> .....	-30 °C to +60 °C (-22°F to +140 °F)
Atmospheric correction	
Temperature range .....	-40 °C to +60 °C (-40 °F to +140 °F)
Barometric pressure .....	400 mmHg to 999 mmHg/533 hPa to 1,332 hPa/15.8 inHg to 39.3 inHg
Dust and water protection .....	IP66

## Certification

Class B Part 15 FCC certification, CE Mark approval, C-Tick.	
Laser safety IEC 60825-1 am2:2007	
Nivo <sup>2,M+</sup> Prism mode: Class 1 laser	
Nivo <sup>2,M+</sup> Reflectorless / Laser Pointer: Class 3R laser	
Nivo <sup>3,M+, Nivo<sup>5,M+</sup></sup>	Reflectorless / Prism mode: Class 1 laser
Nivo <sup>3,M+, Nivo<sup>5,M+</sup></sup>	Laser Pointer: Class 2 laser
Laser Plummets (optional): Class 2 laser	
Bluetooth type approvals are country specific.	

i Good conditions (good visibility, overcast, twilight, underground, low ambient light).  
ii Measuring distance may vary depending on targets and measuring conditions.

iii Kodak Gray Card, Catalog number E1527795

iv Normal conditions (normal visibility, object in the shadow, moderate ambient light).

v Difficult conditions (haze, object in direct sunlight, high ambient light).

vi ±(3+3 ppm x D) mm -20 °C to -10 °C, +40 °C to +50 °C (-4 °F to +14 °F, +104 °F to +122 °F)

vii Measuring time may vary depending on measuring distance and conditions. For the initial measurement, it may take a few more seconds.

viii Measured to KGC 90% at 20 m (65 ft).

ix Battery life specification at 25 °C (77 °F). Operation time may be shorter in low temperatures or if the battery is not new.



## Contact Information:

### AMERICAS

**Spectra Precision Division**  
10368 Westmoor Drive  
Westminster, CO 80021, USA  
+1-720-587-4700 Phone  
888-477-7516 (Toll Free in USA)

[www.spectraprecision.com](http://www.spectraprecision.com)

Specifications subject to change without notice.  
©2014, Trimble Navigation Limited. All rights reserved. Nikon is a registered trademark of Nikon Corporation. All other trademarks are the property of their respective owners. (2014/10)

### EUROPE, MIDDLE EAST AND AFRICA

**Spectra Precision Division**  
Rue Thomas Edison  
ZAC de la Fleuraye - CS 60433  
44474 Carquefou (Nantes), France  
+33 (0)2 28 09 38 00 Phone

### ASIA-PACIFIC

**Spectra Precision Division**  
80 Marine Parade Road  
#22-06, Parkway Parade  
Singapore 449269, Singapore  
+65-6348-2212 Phone

